

**CMOS Color  
Dome Camera**

**NCDIR - P1030N - LK4**



**Feature**

1. Low power consumption.
2. Small board size 32mm x32mm
3. Total Pixel Array: 648\*488
4. Auto gain control.
5. Auto tracing white balance.
6. Back light compensation.
7. Flicker Cancellation Function.

**Specification**

Model	NCDIR - P1030N - LK4
PCB Size	32 x 32 mm
Camera Sensor	1/4" CMOS Sensor
Total Pixel Array	648*488
Sensor Output Image Size	320*240
Auto White Balance	ON
Gamma	0.45
AGC (Auto Gain Control)	ON
Auto Exposure Control	ON
BLC (Back Light Compensation)	ON
Flicker Cancellation	Auto
Power Requirements	DC12V±1V
Power Consumption	70mA
Lens Furnished	Board lens f 4.0mm
Video Out	1 Vp-p Composite Video / 75 Ω
Operating Temperature	0°C to 60°C
Storage Temperature	-10°C to 70°C
Humidity	Under 80% RH (non condensing)


**TEL: (852)2782 7522**

**[www.profitoa.com.hk](http://www.profitoa.com.hk)**

**Packing List**

NO.	Description	Component NO.	Q`TY
1.	CMOS Color Dome Camera	NCDIR - P1030N - LK4	1
2.	Screw & Anchor	Screw - Ancor	3
3.	Manual	NCDIR - Manual	1

**Rear View**



**Dimension(unit:mm)**

