

UFO Dome Camera


NUFO - BN332M SS332M SH332H - L3 BN332H



Feature

1. Color Camera PCB Module with SONY 1/3" SuperHAD CCD Sensor & SHARP 1/3" High Res. CCD Sensor.
2. Employs Digital Signal Processor (DSP) IC for image control.
3. High sensitivity, low smear, high anti-blooming, high S/N ratio.
4. Supports functions: Auto Electronic Shuttler (AES), Auto Gain Control (AGC), Auto White Balance (AWB), Back Light Compensation (BLC), Flicker Less (FL), Mirror function.

Rear View



Specification

Model	NUFO - BN332M SS332M	NUFO - SH332H BN332H
Image Pick-up Device	SHARP 1/3" CCD SONY 1/3" CCD	SONY 1/3" CCD SHARP 1/3" CCD
Effective Picture Elements	NTSC:510*492 PAL:500*582(H*V)	NTSC:768*494 PAL:752*582(H*V)
Horizontal Resolution	420 TV lines	480 TV lines
Minimum Illumination	0.1 LUX @ F2.0	0.5 LUX @ F2.0
S/N Ratio	More than 48dB	More than 48dB
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s ; PAL: 1/50s~1/110,000s	
Auto Gain Control	Automatically	
Auto White Balance	Color Temperature: 2500°K~9500°K	
Gama Characteristic	0.45	
Synchronous System	Internal, Negative sync	
Video Output	1 Vp-p Composite Video / 75 Ω	
Power Supply	12V DC±1V	
Power Consumption	80mA 120mA	100mA
Lens Furnished	Board lens f3.6mm / F 2.0	
Operating Temperature	-10°C to 50°C (14°F to 122°F)	

Packing List

TEL: (852)2782 7522
www.profitoa.com.hk

NO.	Description	Component NO.	Q`TY
1.	UFO Dome Camera	NUFO - BN332M SS332M SH332H BN332H - L3	1
2.	Screw & Anchor	Screw - Ancor	3
3.	Manual	NUFO - Manual	1

Dimension(unit:mm)

